

## Island Stone Pebble Laying Guide (excludes stacked pebble)

**Inspection:** No two pieces of natural stone are exactly alike. Tiles must be examined prior to installation to determine if blending is required. **No claims will be accepted by Island Stone after installation. Use of product implies acceptance.**

**Substrate:** **Floor installations:** The substrate must comply with drying times of BS 5385 & BS 8204-1:2003.

**Wall installations:** As the tiles with adhesive, weigh approximately 23-28 kg p/m<sup>2</sup>, the chosen substrate must have a suitable weight rating.

The substrate must comply with drying times, such as B2 5385 & BS 8204-01

Gypsum  fibre  board and lightweight tile backing boards may be suitable (if) their published weight ratings comply. Block walls, brick walls are normally suitable provided they comply with the weight ratings. Marine ply is generally not an  ideal  product for cement adhesive cohesion and ply manufacturer weight ratings vary widely, unless treated and primed properly ply is subject to warping we therefore do not promote its use.

We recommend 20mm Wedi Tilebacker board as accredited under BBA certificate 00/3675\*. Any application over 3m high we  only  recommend Wedi board 20mm with 12 Wedi approved PW60 washers and Wedi approved fasteners p/m<sup>2</sup> in accordance with their specifications. Note: 12 fixings p/m<sup>2</sup> is a Wedi specification especially for Island Stone products therefore this number of fixings supersedes Wedi's generic general instructions.

For shower enclosures we only recommend Wedi products as per their installation guides.

See [www.wedi.co.uk](http://www.wedi.co.uk)

**Fixing:** **Adhesive** -  Ardex  recommend Ardex S 16 (S16 W white or S16 G grey) together with the flexible additive  Ardex  E90 is proposed for internal conditions. We recommend using a coloured adhesive similar to the stone colour to visually mask any joints (if any).  Ardex  X7R is the recommended adhesive for wet or external conditions.



**Grout** -  Ardex  C 2 (various colours available) with  Ardex  E101 flexible additive.

**Stockist** - For your local stockist and further technical advice on Ardex call 01440 714 939 or visit [www.ardex.co.uk](http://www.ardex.co.uk)

**Movement:** Installers need to accommodate the latest movement building standards into their installation where applicable.

**Installation:** Ensure that each tile butts firmly against the neighbouring tile(s) making sure that as many pebbles as possible are touching the neighbouring tile. Ensure the adhesive protrudes the mesh to make contact with each pebble. Lay only 1m<sup>2</sup> at a time making sure that the adhesive stays WET and does not skin.

Grout and then  sponge off aggressively up to the maximum girth of the pebble , or until the satisfactory visual result is achieved. Use a complimentary non-contrasting grout colour with the pebble colour. For example white grout with black pebbles is NOT recommended, whereas shades of grey to black grout would be more suitable.



**Sealers:** It is recommended that the tiles are sealed with your choice of natural stone sealers. For example Lithofin MN Stain-Stop seals and keeps the stone relatively unchanged in appearance. MN Stain-Stop PLUS (the PLUS aspect is an added colour enhancer) intensifies the colour of the stone.

It is advised to test your choice of sealer first in an area to ensure the chosen sealer is providing the desired finish. For your local stockist and further technical advice on Lithofin products call 01962 732 126 or visit [www.lithofin.com](http://www.lithofin.com)

**Cleaning:** It is recommended that a PH neutral cleaner is used, be wary of acid based cleaners they will break down the sealer over time. PH Neutral cleaners available from Lithofin are Easy-Care (for general purpose maintenance) or Lithofin Wexa for a commercial clean, this probably is only needed at floor level where enthusiastic mopping may have tarnished the visual appearance of the bottom layer of tiles. Otherwise general dusting is all that may be required for the lifetime of the wall. Shower enclosures and floor installations will require routine cleaning with the above PH neutral products, definitely no bleach products allowed.

### Disclaimer

Island Stone's scope of qualified information is limited to the tile itself. Island Stone is not an authoritative source of other manufacturer technical specifications. Island Stone has sought information from Ardex and Wedi systems and uses this information in good faith. Information with regards to fixing, adhesives, build standards or methods, substrate loadings, tolerances and engineering issues are outside of our scope of expertise. Contractors need to ensure by their own enquires that all aspects of installation abide by the latest building standards/interpretations and comply with the other suppliers recommendations.

\*internal use